

Coaxial Termination

DC-26.5GHz/SMA Male/10W

Model:TT10-26.5-S

The TT10-26.5-S is a well-matched, 50Ω male termination enabling operation from DC to 26.5 GHz. This termination features a 10W power rating and 1.3:1 max VSWR.

Features:

- Operating Frequency DC to 26.5 GHz
- High Return Loss
- Instrumentation Grade

Applications:

- laboratory test
- Communication equipment


电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency Range	DC		26.5	GHz
驻波 VSWR			1.3	:1
耐功率 Power Handling			10	W
阻抗 Impedance		50		Ohms

环境和机械特性 Envrionmental And Physical Characteristics:

类型 Description	参数 Parameter	单位 Units
操作温度 Operating Temperature	-55 To +125	℃
存储温度 Storage Temperature	-55 To +125	℃
壳体 Body Material	Black, Finned Aluminum	
接口 Connectors	SMA Male	
中心导体 Center Conductor	Gold-plated brass	
相对湿度 Relative Humidity	0-90%	

外形图 Outline Drawing: Unit:mm



订货信息 Ordering Information:

标准型号 Base Number	描述 Description
TT10-26.5-S	DC-26.5GHz,10W,SMA male Coaxial Termination