

## Solid State High Power Amplifier Systems

1-6GHz/57dB Gain/57dBm Psat/380V AC

Model: TLPA1G6G-57-57-BC

TLPA1G6G-57-57-BC is a solid state high power amplifier systems provides high output power and high gain across the 1 to 6 GHz frequency range. The amplifier features a built-in 380V power supply, making it easy to use in most lab environments. This model features thermal self protection, preventing damage to the amplifier and providing added reliability.

### Features:

- Frequency range: 1-6GHz
- Gain: 57dB Min
- Psat Output Power: 57dBm Min
- Protection: Over TEM, over voltage, over current, over VSWR protection
- 50 Ohm Matched Input / Output

### Electrical Characteristics:

Parameter	Symbol	Min	Typ	Max	Units
Frequency range	BW	1-6			GHz
Power Gain	GP	57			dB
Gain flatness	$\Delta$ GL		$\pm 3$		dB
Gain adjust Range	$\Delta$ GR		30		dB
Gain adjust Step	$\Delta$ GS		0.5		dB
Output Psat	Psat	57			dBm
Output P1dB	P1dB		52		dBm
Spurious	Spur			-60	dBc
Harmonics	HAM		-15	-10	dBc
Input VSWR	VSWR <sub>in</sub>			2.0	:1
AC Voltage	Vac		380		V AC
Impedance	I/O-IMP	50			Ohms

### Mechanical Specifications:


Parameter	Value	Units
Input /Output Connector	N Female/L29 Female	
Size	12U	
Weight	$\leq 150$	Kg

### Absolute Maximum Ratings:

Parameter	Value
RF Input Power	+5 dBm
ESD sensitivity (HBm)	Class 0, passed 150V

### Outline Drawing:

Unit:mm



### Key Features:

Parameter	Advantages
Control functions	1, Power setting On/Off 2, ALC automatic level control
Protection functions	1, Over TEM 2, Over voltage 3, Over current 4, Over VSWR
Remote control	RS422/Ethernet
Cooling system	Built in Cooling system, forced air cooling

### Environmental Conditions:

Parameter	Min	Typ	Max	Units
Operating Temperature*	-20		+40	°C
Non-operating Temperature*	-30		+50	°C
Relative humidity		95		%
Altitude	10,000			feet
Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

\*Note: For a wider temperature range, please consult the manufacturer.

### Ordering Information:

Base Number	Description	Revision
TLPA1G6G-57-57-BC	Solid State High Power Amplifier Systems 0.5-6GHz, Gain:57dB, Psat:57dBm, 380V AC, Built in Fan Cooling	Rev.1.1