

Solid State High Power Amplifier Systems

1-500MHz /54dB Gain/54 dBm Psat/220V AC

Model: TLPA1M500M-54-54-BC

TLPA1M500M-54-54-BC is a solid state high power amplifier systems provides high output power and high gain across the 1 to 500 MHz frequency range. The amplifier features a built-in 220V power supply, making it easy to use in most lab environments. This model features thermal self protection, preventing damage to the amplifier and providing added reliability.

Features:

- Wide Band: 1-500 MHz
- Gain: 54dB Min
- Psat Output Power:54dBm Min
- Protection:Over TEM,over voltage, over current protection
- 50 Ohm Matched Input / Output

Electrical Characteristics:

Parameter	Symbol	Min	Typ	Max	Units
Frequency range	BW	1-500			MHz
Power Gain	SSGP	54			dB
Gain flatness	Δ GL		± 2	± 3	dB
Output Psat	Psat	54			dBm
Output P1dB	P1dB		50		dBm
Spurious@Pout=54dBm	Spur			-60	dBc
Harmonics@Pout=54dBm	HAM			-10	dBc
Input VSWR	VSWRin		1.5	2	:1
AC Voltage	Vac	110	220		V AC
AC Supply Current	Iac		5		A
Impedance	I/O-IMP	50			Ohms


Mechanical Specifications:

Parameter	Value	Units
Input /Output Connector	N Female/N Female	
Size	4U*500 depth	mm
Weight	≤ 10	Kg

Absolute Maximum Ratings:

Parameter	Value
RF Input Power	+5 dBm
ESD sensitivity (HBm)	Class 0, passed 150V

Outline Drawing: Unit:mm



Key Features:

Parameter	Advantages
Control functions	1, Power setting On/Off 2,ALC automatic level control
Protection functions	1,Over TEM 2,Over voltage 3,Over current
Remote control	RS422/Ethernet
Cooling system	Built in Cooling system,forced air cooling

Environmental Conditions:


Parameter	Min	Typ	Max	Units
Operating Temperature*	-20		+40	°C
Non-operating Temperature*	-30		+50	°C
Relative humidity		95		%
Altitude	10,000			feet
Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

*Note: For a wider temperature range, please consult the manufacturer.

Ordering Information:

Base Number	Description	Revision
TLPA1M500M-54-54-BC	Solid State High Power Amplifier Systems 1-500MHz,Gain:54dB,Psat:54 dBm,220V AC,Built in Fan Cooling	Rev.1.1


Typical Performance Data:




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

Typical Performance Data:


Small Signal Gain vs Frequency



Gain vs Output Power




Psat vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

Typical Performance Data:

3rd Harmonics vs Output Power



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.