

## E-band Spectrum Frequency Extension Systems

60-90GHz/WR-12

Model: TLSM-060090-08-12

TLSM-060090-08-12 spectrum frequency extension systems are a dedicated Test & Measurement solution for extending the range of your signal source to 60-90GHz.

### Features:

- Frequency range: 60-90GHz
- Conversion Loss SSB: 9dB Typ
- Low conversion loss

### Applications:

- Frequency Extension
- Antenna measurements
- Material characterisation

### 电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	60		90	GHz
中频输出频率 IF Output Frequency	DC		5	GHz
本振输入频率 LO Input Frequency	7.5		11.25	GHz
本振输入功率 LO Input Power	13	15	20	dBm
倍频次数 Multiplication Factor		8		
射频输入功率 RF Input Power		-10	0	dBm
变频损耗 Mixer Conversion Loss SSB		9		dB


### 机械特性 Mechanical Specifications:

描述 Description	参数 Parameter	单位 Units
射频输入端口 RF Input Ports	WR-12/UG-387/U	
本振/中频端口 LO/IF Ports	SMA Female	
本振输入端口 LO Input Ports	SMA Female	
中频输出端口 IF Output Ports	SMA Female	
供电引脚 Power Supply Pin	FGG 0B 4 Core	
尺寸 Size	155.2*75.2*52	mm


**绝对最大值 Absolute Maximum Ratings :**

参数 Parameter	指标 Value
供电电压 Supply Bias Voltage	+240 V AC
射频输入功率 RF Input Power	0 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

**外形图 Outline Drawing: Unit:mm**



**原理框图 Block Diagrams:**



## 环境和物理特性 Environmental And Physical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-10		+65	°C
存储温度 Non-operating Temperature	-45		+85	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

## 订货信息 Ordering Information:

标准型号 Part Number	描述 Description	版本号 Revision
TLSM-060090-08-12	E-Band Spectrum Frequency Extension Systems X8,60-90GHz, Conversion Loss SSB: 9dB typ.	Rev.1.2

## 随货配件 Components Included:

标准型号 Part Number	描述 Description	数量 Quantity
TACTDC-22012	AC-to-DC Power Adapter	1 PCS