

Low Noise Amplifier

18-50GHz/5.0dB NF/23dB Gain/13dBm P1dB

Model: TLLA18G50G-22-50

TLLA18G50G-22-50 is a low noise amplifier with a typical small signal gain of 23 dB and a nominal noise figure of 5.0 dB across the frequency range of 18 to 50 GHz. The DC power requirement for the amplifier is +5 V DC/180 mA. The input and output port configuration offers coax adapter structure with 2.4mm female.

Features:

- Frequency range: 18-50GHz
- Gain: 23dB Typ
- Noise Figure: 5.0dB Typ
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Communication systems

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	18		50	GHz
小信号增益 Small Signal Gain	20	23		dB
增益平坦度 Gain Flatness		±2.5		dB
噪声系数 Noise Figure		5		dB
线性输出功率 Output P1dB	13	14		dBm
饱和输出功率 Output Psat		15		dBm
输入驻波 Input VSWR		2		:1
输出驻波 Output VSWR		2		:1
直流电压 DC Voltage		+5	+8	V DC
直流电流 DC Supply Current		180		mA
阻抗 Impedance		50		Ohms

机械特性 Mechanical Specifications:


参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	2.4mm Female/2.4mm Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	44.8*29.2*11	mm

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+8 V
输入功率 RF Input Power	+5 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing:

Unit:mm



*****Heat Sink Required During Operation**



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-45		+85	°C
存储温度 Non-operating Temperature	-55		+125	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	50,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLLA18G50G-22-50	Low Noise Amplifier, 18-50GHz, Noise Figure:5.0dB, Gain:23 dB,P1dB:13dBm,+5V DC,Without Heatsink	Rev.1.1
TLLA18G50G-22-50-HS	Low Noise Amplifier, 18-50GHz, Noise Figure:5.0dB, Gain:23 dB,P1dB:13dBm,+5V DC,With Heatsink	Rev.1.1