

## Low Noise Amplifier

2-40GHz/5.5dB NF/30dB Gain/19dBm P1dB

Model: TLLA2G40G-30-45

TLLA2G40G-30-45 is a low noise amplifier with a minimum small signal gain of 30 dB and a nominal noise figure of 5.5 dB across the frequency range of 2 to 40 GHz. The DC power requirement for the amplifier is +12 V DC/240 mA. The input and output port configuration offers coax adapter structure with 2.92mm female.

### Features:

- Frequency range: 2-40GHz
- Gain: 30dB Min
- Noise Figure: 5.5dB Typ
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

### Applications:

- Communication systems

### 电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	2		40	GHz
小信号增益 Small Signal Gain	30	33		dB
增益平坦度 Gain Flatness		±2.5	±5.5	dB
噪声系数 Noise Figure		5.5	6	dB
线性输出功率 Output P1dB	15	19		dBm
饱和输出功率 Output Psat		20		dBm
杂散 Spurious		-60		dBc
输入驻波 Input VSWR		1.8	2.2	:1
输出驻波 Output VSWR		1.8	2.5	:1
直流电压 DC Voltage		+12		V DC
直流电流 DC Supply Current		240		mA
阻抗 Impedance		50		Ohms

### 机械特性 Mechanical Specifications:


参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	2.92mm Female/2.92mm Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	35.3*40.3*12	mm

## 绝对最大值 Absolute Maximum Ratings:


参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	TBD
输入功率 RF Input Power	0 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V



## 外形图 Outline Drawing: Unit:mm



**\*\*\*Heat Sink Required During Operation**



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

## 温度环境 Environmental Conditions:


参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-25		+85	°C
存储温度 Non-operating Temperature	-55		+125	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	50,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

### 订货信息 Ordering Information:


标准型号 Base Number	描述 Description	版本号 Revision
TLLA2G40G-30-45	Low Noise Amplifier, 2-40GHz, Noise Figure:5.5dB, Gain:30 dB,P1dB:19dBm,+12V DC,Without Heatsink	Rev.1.1
TLLA2G40G-30-45-HS	Low Noise Amplifier, 2-40GHz, Noise Figure:5.5dB, Gain:30 dB,P1dB:19dBm,+12V DC,With Heatsink	Rev.1.1

### 典型曲线 Typical Performance Data:

#### Gain&VSWR vs Frequency




#### Noise Figure vs Frequency




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:


Gain vs Output Power



P1dB vs Frequency




P3dB vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

## 典型曲线 Typical Performance Data:

### Psat vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.