

Low Noise Amplifier

3-8GHz/0.9dB NF/21dB Gain/17dBm P1dB

Model: TLLA3G8G-21-09

TLLA3G8G-21-09 is a low noise amplifier with a typical small signal gain of 21 dB and a nominal noise figure of 0.9 dB across the frequency range of 3 to 8 GHz. The DC power requirement for the amplifier is +8 V DC/50 mA. The input and output port configuration offers coax adapter structure with SMA female.

Features:

- Frequency range: 3-8GHz
- Gain: 21dB Typ
- Noise Figure: 0.9dB Typ
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Communication systems

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	3		8	GHz
小信号增益 Small Signal Gain	20	21		dB
增益平坦度 Gain Flatness		±1.0		dB
噪声系数 Noise Figure		0.9		dB
线性输出功率 Output P1dB	16	17		dBm
饱和输出功率 Output Psat	17	18		dBm
输入驻波 Input VSWR		2.5		:1
输出驻波 Output VSWR		2		:1
直流电压 DC Voltage	+5.5	+8	+12	V DC
直流电流 DC Supply Current		50		mA
阻抗 Impedance		50		Ohms

机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	SMA Female/SMA Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	28*20*10	mm

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLLA3G8G-21-09	Low Noise Amplifier, 3-8GHz, Noise Figure:0.9dB, Gain:21dB,P1dB:17dBm,+8V DC,Without Heatsink	Rev.1.1
TLLA3G8G-21-09-HS	Low Noise Amplifier, 3-8GHz, Noise Figure:0.9dB, Gain:21dB,P1dB:17dBm,+8V DC,With Heatsink	Rev.1.1

典型曲线 Typical Performance Data:

Gain&VSWR vs Frequency




Noise Figure vs Frequency




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:


Gain vs Output Power



P1dB vs Frequency




P3dB vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.