

## Low Noise Amplifier

4-8GHz/0.7dB NF/26dB Gain/10dBm P1dB

Model: TLLA4G8G-26-07

TLLA4G8G-26-07 is a low noise amplifier with a typical small signal gain of 26 dB and a nominal noise figure of 0.7 dB across the frequency range of 4 to 8 GHz. The DC power requirement for the amplifier is +8 V DC/35 mA. The input and output port configuration offers coax adapter structure with SMA female.

### Features:

- Frequency range: 4-8GHz
- Gain: 26dB Typ
- Noise Figure: 0.7dB Typ
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

### Applications:

- Communication systems

### 电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	4		8	GHz
小信号增益 Small Signal Gain	25	26		dB
增益平坦度 Gain Flatness		±1.0	±1.5	dB
噪声系数 Noise Figure		0.7		dB
线性输出功率 Output P1dB	10			dBm
输出三阶交调 Output IP3		25		dBm
输入驻波 Input VSWR		1.5	2	:1
输出驻波 Output VSWR		1.5	2.2	:1
直流电压 DC Voltage		+8		V DC
直流电流 DC Supply Current		35		mA
阻抗 Impedance		50		Ohms

### 机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	SMA Female/SMA Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	44.8*29.2*11	mm
重量 Weight	55	g


## 绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+15 V
输入功率 RF Input Power	+2 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V



## 外形图 Outline Drawing:

Unit:mm



## \*\*\*Heat Sink Required During Operation



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

## 温度环境 Environmental Conditions:


参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-45		+85	°C
存储温度 Non-operating Temperature	-55		+125	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	50,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

## 订货信息 Ordering Information:


标准型号 Base Number	描述 Description	版本号 Revision
TLLA4G8G-26-07	Low Noise Amplifier, 4-8GHz, Noise Figure:0.7dB, Gain:26dB,P1dB:10dBm,+8V DC,Without Heatsink	Rev.1.1
TLLA4G8G-26-07-HS	Low Noise Amplifier, 4-8GHz, Noise Figure:0.7dB, Gain:26dB,P1dB:10dBm,+8V DC,With Heatsink	Rev.1.1

## 典型曲线 Typical Performance Data:

### Gain&VSWR vs Frequency




### Noise Figure vs Frequency




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

## 典型曲线 Typical Performance Data:

### Gain vs Output Power



### P1dB vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.