

Power Amplifier

20-50GHz/23dB Gain/23dBm Psat

Model: TLPA20G50G-23-23

TLPA20G50G-23-23 is a power amplifier with a typical small signal gain of 23 dB and a nominal Psat of 23 dBm across the frequency range of 20 to 50 GHz. The DC power requirement for the amplifier is +6 VDC/420 mA. The input and output port configuration offers coax adapter structure with 2.4mm female.

Features:

- Frequency range: 20-50GHz
- Gain: 23dB Typ
- Output Power Psat: 23dBm Typ
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Cellular
- PCN
- GSM
- ISM
- Lab Test

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	20		50	GHz
小信号增益 Small Signal Gain	20	23		dB
增益平坦度 Gain Flatness		±3		dB
线性输出功率 Output P1dB	20.5	21		dBm
饱和输出功率 Output Psat	21	23		dBm
驻波 VSWR		2.3		:1
直流电压 DC Voltage	5	6	8	V DC
直流电流 DC Supply Current		420		mA
阻抗 Impedance		50		Ohms

机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	2.4mm Female/2.4mm Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	44.8*29.2*11	mm


绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+8 V
输入功率 RF Input Power	+13 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V



外形图 Outline Drawing:

Unit:mm



*****Heat Sink Required During Operation**



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

温度环境 Environmental Conditions:


参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-40		+60	°C
存储温度 Non-operating Temperature*	-50		+70	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

*Note: For a wider temperature range, please consult the manufacturer.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLPA20G50G-23-23	Power amplifier 20-50GHz, Gain:23dB,Psat:23dBm,+6V DC,Without Heatsink	Rev.1.0
TLPA20G50G-23-23-HS	Power amplifier 20-50GHz, Gain:23dB,Psat:23dBm,+6V DC,With Heatsink	Rev.1.0


典型曲线 Typical Performance Data:




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:


Gain vs Output Power



P1dB vs Frequency




P3dB vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:

Psat vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.