

Power Amplifier

0.3-5GHz /25dB Gain/32dBm Psat

Model: TLPA0.3G5G-25-32

TLPA0.3G5G-25-32 is a power amplifier with a minimum small signal gain of 25 dB and a minimum Psat of 32 dBm across the frequency range of 0.3 to 5 GHz. The DC power requirement for the amplifier is +12 VDC/0.7 A. The input and output port configuration offers coax adapter structure with SMA female.

Features:

- Frequency range: 0.3-5GHz
- Gain: 25dB Min
- Output Power Psat: 32dBm Min
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Cellular
- PCN
- GSM
- ISM
- Lab Test

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	0.3		5	GHz
小信号增益 Small Signal Gain	25			dB
增益平坦度 Gain Flatness		±2.0		dB
线性输出功率 Output P1dB		30		dBm
饱和输出功率 Output Psat	32			dBm
输入驻波 Input VSWR		1.8		:1
输出驻波 Output VSWR		1.8		:1
直流电压 DC Voltage	+9	+12	+15	V DC
直流电流 DC Supply Current		0.7	0.9	A
阻抗 Impedance		50		Ohms

机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	SMA Female/SMA Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	30*50*12	mm


绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+15 V
输入功率 RF Input Power	+14 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V



外形图 Outline Drawing:

Unit:mm



*****Heat Sink Required During Operation**



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-40		+60	°C
存储温度 Non-operating Temperature*	-50		+70	°C
相对湿度 Relative humidity	100%RH at 35°C, 95%RH at 40°C			%
海拔 Altitude	50,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

*Note: For a wider temperature range, please consult the manufacturer.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLPA0.3G5G-25-32	Power amplifier 0.3-5GHz, Gain:25dB,Psat:32dBm,+12V DC,Without Heatsink	Rev.1.1
TLPA0.3G5G-25-32-HS	Power amplifier 0.3-5GHz, Gain:25dB,Psat:32dBm,+12V DC,With Heatsink	Rev.1.1