



### Electrical & Environmental Characteristics

Impedance	50 Ω
Insulation Resistance	5000 MΩ
Operating Frequency	DC~67GHz
Dielectric Withstanding Voltage	1000V
VSWR	≤1.15
Insertion Loss	≤0.05* $\sqrt{f\_GHz}$
Operating Temperature	- 55~+165°C

### Material & Coat-Plating

Inner Conductor	Beryllium Copper, Gold
Dielectric	PEI 1000
Body	Stainless Steel, Passivated
Coupling Nut	Stainless Steel, Passivated

No.	Model	Pin Size Ød
1	1.85-JFD80609	0.23 [0.009]
2	1.85-JFD80612	0.30 [0.012]

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Suzhou Talent Microwave, Inc			
		CHK				
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ± 3 PLC ± ANGLES ±1°	APVD	Product Model  <b>1.85-JFD80612</b> <b>1.85mm male Flange Connector</b>			
MATERIAL SEE TABLE	FINISH SEE TABLE	PRODUCT SPEC	SIZE A4	GAGE CODE OT8L4	DRAWING NO	
		APPLICATION SPEC	CUSTOMER DRAWING		SHEET 1 OF 1	RVE 1