

Power Amplifier

15-44GHz/25dB Gain/20dBm P1dB

Model: TLPA15G44G-25-20

TLPA15G44G-25-20 is a power amplifier with a typical small signal gain of 25 dB and a nominal P1dB of 20 dBm across the frequency range of 15 to 44 GHz. The DC power requirement for the amplifier is +12 VDC/210 mA. The input and output port configuration offers coax adapter structure with 2.4mm female.

Features:

- Frequency range: 15-44GHz
- Gain: 25dB Typ
- Output Power P1dB: 20dBm Typ
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Cellular
- PCN
- GSM
- ISM
- Lab Test

Electrical Characteristics:

Parameter	Min	Typ	Max	Units
Frequency range	15		44	GHz
Small Signal Gain		25		dB
Gain Flatness		±2.5		dB
Output P1dB		20		dBm
Input VSWR			2.5	:1
Output VSWR			2.5	:1
Harmonics	+10	+12	+13	V DC
DC Voltage		210		mA
Impedance		50		Ohms

Mechanical Specifications:

Parameter	Value	Units
Input /Output Connector	2.4mm Female/2.4mm Female	
DC Bias	Solder Pin	
Size	44*36*12	mm


Absolute Maximum Ratings:

Parameter	Value
Supply Bias Voltage	+15 V
RF Input Power	+20 dBm
ESD sensitivity (HBm)	Class 0, passed 150V



Outline Drawing:

Unit:mm



*****Heat Sink Required During Operation**



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

Environmental Conditions:

Parameter	Min	Typ	Max	Units
Operating Temperature*	-40		+60	°C
Non-operating Temperature*	-50		+70	°C
Relative humidity		95		%
Altitude	10,000			feet
Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			


*Note: For a wider temperature range, please consult the manufacturer.

Ordering Information:

Base Number	Description	Revision
TLPA15G44G-25-20	Power amplifier 15-44GHz, Gain:25dB,P1dB:20dBm,+12V DC,Without Heatsink	Rev.1.1
TLPA15G44G-25-20-HS	Power amplifier 15-44GHz, Gain:25dB,P1dB:20dBm,+12V DC,With Heatsink	Rev.1.1

Typical Performance Data:


VSWR&Gain vs Frequency




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

Typical Performance Data:


Gain vs Output Power



P1dB vs Frequency



P3dB vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.