



### Electrical & Environmental Characteristics

Impedance	50Ω
Insulation Resistance	≥5000MΩ
Operating Frequency	DC~40GHz
Dielectric Withstanding Voltage	325V
VSWR	≤1.25
Hermeticity	≤1.1013x10 <sup>-3</sup> Pa · cm <sup>3</sup> /sHe
Operating Temperature	- 55~+165℃

### Material & Coat-Plating

Inner Conductor	4J29
Dielectric	Glass
Body	4J29

No.	Model	X
1	TLSPMC02	有限擒纵
2		

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Suzhou Talent Microwave, Inc			
		CHK				
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ± 3 PLC ± ANGLES ±1°	APVD	Product Model  <b>TLSPMC02</b> SMP male, HERMETIC SEALED Adaptor			
		PRODUCT SPEC				
		APPLICATION SPEC				
MATERIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	SIZE A4	GAGE CODE 0T8L4	DRAWING NO	
		CUSTOMER DRAWING			SHEET1 OF 1	RVE 1