

Power Amplifier

WR-15/55-66GHz/18dB Gain/23dBm Psat**Model: TMPA-055066-1823-15**

TMPA-055066-1823-15 is a power amplifier with a typical small signal gain of 18 dB and a minimum Psat of 23 dBm across the frequency range of 50 to 75 GHz. The DC power requirement for the amplifier is +5 VDC/1.5A. The input and output port configuration offers an inline structure with WR-15 waveguides and UG-385/U-M antiracking flanges.

Features:

- Frequency range: 55-66GHz
- Gain: 18dB Typ
- Output Power Psat: 23dBm Typ
- Good Power and Gain Flatness

Applications:

- Passive Imaging
- Communication Systems
- Radar Systems

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	55		66	GHz
小信号增益 Small Signal Gain		18		dB
饱和输出功率 Output Psat		23		dBm
输入驻波 Input VSWR		3		:1
输出驻波 Output VSWR		3		:1
直流电压 DC Voltage		5		V DC
直流电流 DC Supply Current		1.5		A

机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	WR-15/UG-385/U	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	TBD	mm

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	TBD
输入功率 RF Input Power	TBD
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing:

Unit:mm; Tolerance:±0.1mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-10		+65	°C
存储温度 Non-operating Temperature	-45		+85	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TPMA-055066-1823-15	Power Amplifier, 55-66GHz, Gain: 18dB Type, Psat: 23dBm Typ, +5V DC,WR-15,Without heatsink	Rev.1.1
TPMA-055066-1823-15-HS	Power Amplifier, 55-66GHz, Gain: 18dB Type, Psat: 23dBm Typ, +5V DC,WR-15,With heatsink	Rev.1.1