

Power Amplifier

WR-10/75-90GHz/17dB Gain/16dBm Psat

Model: TMPA-075090-1716-10

TMPA-075090-1716-10 is a power amplifier with a typical gain of 17 dB and a nominal Psat of 16 dBm across the frequency range of 75 to 90 GHz. The DC power requirement for the amplifier is +12 VDC/70 mA. The input and output port configuration offers an inline structure with WR-10 waveguides and UG-387/U-M antcocking flanges.

Features:

- Frequency range: 75-90GHz
- Gain: 17dB Typ
- Output Power Psat: 16dBm Typ
- Good Power and Gain Flatness

Applications:

- Passive Imaging
- Communication Systems
- Radar Systems

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	75		90	GHz
增益 Gain		17		dB
饱和输出功率 Output Psat		16		dBm
输入驻波 Input VSWR		2.3		:1
输出驻波 Output VSWR		2		:1
直流电压 DC Voltage		12		V DC
直流电流 DC Supply Current		70		mA

机械特性 Mechanical Specifications:


参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	WR-10/UG-387/U	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	30*30*23	mm

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+15 V
输入功率 RF Input Power	+10 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing:

Unit:mm; Tolerance:±0.1mm



*****Heat Sink Required During Operation**



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.


温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-10		+65	℃
存储温度 Non-operating Temperature	-45		+85	℃
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:


标准型号 Base Number	描述 Description	版本号 Revision
TMPA-075090-1716-10	Power Amplifier, 75-90GHz, Gain: 17dB Type, Psat: 16dBm Type, +12V DC,WR-10, Without heatsink	Rev.1.1
TMPA-075090-1716-10-HS	Power Amplifier, 75-90GHz, Gain: 17dB Type, Psat: 16dBm Type, +12V DC,WR-10, With heatsink	Rev.1.1

典型曲线 Typical Performance Data:



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.