

Power Amplifier

WR-10/85-100GHz/38dB Gain/24dBm Psat**Model: TMPA-085100-3826-10-E**

TMPA-085100-3826-10-E is a power amplifier with a typical gain of 38 dB and a nominal Psat of 24 dBm across the frequency range of 85 to 100 GHz. The DC power requirement for the amplifier is +8 VDC/1.2 A. The input and output port configuration offers an inline structure with WR-10 waveguides and UG-387/U-M antcocking flanges.

Features:

- Frequency range: 85-100GHz
- Gain: 38dB Typ
- Output Power Psat: 24dBm Typ
- Good Power and Gain Flatness

Applications:

- Passive Imaging
- Communication Systems
- Radar Systems

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	85		100	GHz
增益 Gain		38		dB
增益平坦度 Gain Flatness		±3		dB
饱和输出功率 Output Psat		24		dBm
直流电压 DC Voltage		8		V DC
直流电流 DC Supply Current		1.2		A

机械特性 Mechanical Specifications:


参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	WR-10/UG-387/U	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	38.1*27.94*19.05	mm

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	TBD
输入功率 RF Input Power	0 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing:

Unit:mm; Tolerance:±0.1mm



*****Heat Sink Required During Operation**



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.


温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-10		+65	°C
存储温度 Non-operating Temperature	-45		+85	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:


标准型号 Base Number	描述 Description	版本号 Revision
TMPA-085100-3826-10-E	Power Amplifier, 85-100GHz, Gain: 38dB Type, Psat: 24dBm Type, +8V DC,WR-10, Without heatsink	Rev.1.1
TMPA-085100-3826-10-E-HS	Power Amplifier, 85-100GHz, Gain: 38dB Type, Psat: 24dBm Type, +8V DC,WR-10, With heatsink	Rev.1.1

典型曲线 Typical Performance Data:



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.