

## Power Amplifier

WR-10/92-96GHz/32dB Gain/30dBm Psat

Model: TMPA-092096-3030-10

TMPA-092096-3030-10 is a power amplifier with a typical small signal gain of 32 dB and a nominal Psat of 30 dBm across the frequency range of 92 to 96 GHz. The DC power requirement for the amplifier is +19 VDC/1.2 A. The input and output port configuration offers an inline structure with WR-10 waveguides and UG-387/U-M antickocking flanges.

### Features:

- Frequency range: 92-96GHz
- Gain: 32dB Typ
- Output Power Psat: 30dBm Typ
- Good Power and Gain Flatness

### Applications:

- Passive Imaging
- Communication Systems
- Radar Systems

### Electrical Characteristics:

Parameter	Min	Typ	Max	Units
Frequency range	92		96	GHz
Small Signal Gain	30	32		dB
Output Psat	29	30	32	dBm
Input VSWR		2		:1
Output VSWR		2.5		:1
DC Voltage		19		V DC
DC Supply Current		1.2		A

### Mechanical Specifications:


Parameter	Value	Units
Input /Output Connector	WR-10/UG-387/U	
DC Bias	Solder Pin	
Size	54*56*42(Without heatsink) 54*99*86(With heatsink)	mm

### Absolute Maximum Ratings:

Parameter	Value
Supply Bias Voltage	TBD
RF Input Power	TBD
ESD sensitivity (HBm)	Class 0, passed 150V

### Outline Drawing:

Unit:mm; Tolerance:±0.1mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

### Environmental Conditions:

Parameter	Min	Typ	Max	Units
Operating Temperature	-10		+65	°C
Non-operating Temperature	-45		+85	°C
Relative humidity		95		%
Altitude	10,000			feet
Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

### Ordering Information:

Base Number	Description	Revision
TMPA-092096-3030-10	Power Amplifier, 92-96GHz, Gain: 32dB Type, Psat: 30dBm Type, +19V DC,WR-10, Without heasink	Rev.1.1
TMPA-092096-3030-10-HS	Power Amplifier, 92-96GHz, Gain: 32dB Type, Psat: 30dBm Type, +19V DC,WR-10, With heasink	Rev.1.1