

Coaxial Band-pass Filter

8.995-9.005GHz/ SMA Female

Model: TLBF-9G-10M-E

TLBF-9G-10M-E is a coaxial band-pass filter with a passband frequency from 8.995 to 9.005GHz and a rejection frequencies at 9.2GHz. The nominal insertion loss(fo) of the filter is 2.5 dB and the typical rejection is 35 dB.

Features:

- Passband Frequency Range 8.995 to 9.005GHz
- Low Insertion Loss
- High Rejection
- Steep Rejection Skirts

Applications:

- Instrumentations
- Radar Systems
- System Integrations

Electrical Characteristics:


Parameter	Min	Typ	Max	Units
Passband Frequency range	8.995		9.005	GHz
Passband Insertion Loss			2.5	dB
Pass Band Ripple			1.8	dB
Rejection	>35dB@9.2GHz			dB
Power Handling			15	W
Input VSWR			1.5	:1
Output VSWR			1.5	:1
Impedance	50			Ohms

Envrionmental And Physical Characteristics:

Description	Parameter	Units
Operating Temerature	-40 To +70	°C
Storage Temperature	-40 to +70	°C
Connectors	SMA Female	

Outline Drawing:

Unit:mm;




ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

Ordering Information:

Base Number	Description	Revision
TLBF-9G-10M-E	Coaxial Band-pass Filter, Passband frequency range: 8.995 to 9.005 GHz, Passband Insertion Loss(f0): 2.5 dB, SMA Female	Rev.1.0

Typical Performance Data:



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.