

Coaxial Band-pass Filter

17.7-21.2 GHz/SMA

Model: TLBF-17G7-21G2-A

TLBF-17G7-21G2-A is a coaxial band-pass filter with a passband frequency from 17.7 to 21.2 GHz and a rejection frequencies from DC-16.2 GHz and 22.7 GHz. The maximum fo insertion loss of the filter is 1.5 dB and the typical rejection is 25 dB.

Features:

- Passband Frequency Range 17.7 to 21.2 GHz
- Low Insertion Loss
- High Rejection
- Steep Rejection Skirts

Applications:

- Instrumentations
- Radar Systems
- System Integrations

电气特性 Electrical Characteristics:


参数 Parameter	Min	Typ	Max	单位 Units
通带频率范围 Passband Frequency range	17.7		21.2	GHz
带宽 Band Width			3.5	GHz
插损 Insertion Loss		1.2	1.5	dB
带内波动 Pass Band Ripple			1.0	dB
带外抑制 Rejection	≥50dB@DC-16.2GHz &22.7GHz			dB
耐受功率 Power Handling			20	W
驻波 VSWR			1.6	:1
阻抗 Impedance	50			Ohms

环境和机械特性 Envriionmental And Physical Characteristics:

类型 Description	参数 Parameter	单位 Units
操作温度 Operating Temperature	-40 To +70	°C
接口 Connectors	SMA	

外形图 Outline Drawing:

Unit:mm




ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLBF-17G7-21G2-A	Coaxial Band-pass Filter, Passband frequency range: 17.7-21.2GHz, Passband Insertion Loss: 1.5dB, SMA	Rev.1.0

典型曲线 Typical Performance Data:



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.