

Coaxial Band-pass Filter

1.3-3 GHz/SMA Female

Model: TLBF-1G3-3G-X

TLBF-1G3-3G-X is a coaxial band-pass filter with a passband frequency from 1.3 to 3 GHz and a rejection frequencies from DC to 0.6 GHz and from 3.6 to 6 GHz. The maximum insertion loss of the filter is 1.5 dB and the minimum rejection is 50 dB.

Features:

- Passband Frequency Range 1.3 to 3 GHz
- Low Insertion Loss
- High Rejection
- Steep Rejection Skirts

Applications:

- Instrumentations
- Radar Systems
- System Integrations


电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
通带频率范围 Passband Frequency range	1.3		3	GHz
通带插损 Passband Insertion Loss			1.5	dB
带内纹波 Pass Band Ripple			1.0	dB
驻波 VSWR			1.8	:1
带外抑制 Rejection@DC-0.6GHz&3.6-6GHz	50			dB
耐受功率 Power Handling			15	W
阻抗 Impedance	50			Ohms

环境和机械特性 Envirionmental And Physical Characteristics:

类型 Description	参数 Parameter	单位 Units
操作温度 Operating Temperature	-40 To +70	°C
接口 Connectors	SMA Female	
尺寸 Size	12*43*118	mm

外形图 Outline Drawing: Unit:mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLBF-1G3-3G-X	Coaxial Band-pass Filter, Passband frequency range: 1.3-3GHz, Passband Insertion Loss: 1.5dB, SMA Female	Rev.1.0