

Coaxial Band-pass Filter

1300-1400 MHz/SMA Female

Model: TLBF-1G35-100M-L

TLBF-1G35-100M-L is a coaxial band-pass filter with a passband frequency from 1300 to 1400 MHz and a rejection frequencies from DC to 1050 MHz and from 1650 to 4000 MHz. The maximum insertion loss of the filter is 3.0 dB and the minimum rejection is 35 dB.

Features:

- Passband Frequency Range 1300 to 1400 MHz
- High Rejection
- Steep Rejection Skirts

Applications:

- Instrumentations
- Radar Systems
- System Integrations


电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
通带频率范围 Passband Frequency range	1300		1400	MHz
带宽 Band Width			100	MHz
插损 Insertion Loss(f0)			3.0	dB
带内纹波 Pass Band Ripple			2.3	dB
驻波 VSWR			1.6	:1
带外抑制 Rejection@DC-1050MHz&1650-4000MHz	35			dB
耐受功率 Power Handling			2	W
阻抗 Impedance	50			Ohms

环境和机械特性 Envrionmental And Physical Characteristics:

类型 Description	参数 Parameter	单位 Units
操作温度 Operating Temerature	-40 To +70	°C
接口 Connectors	SMA Female	
尺寸 Size	10*12*40.4	mm

外形图 Outline Drawing: Unit:mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLBF-1G35-100M-L	Coaxial Band-pass Filter, Passband frequency range: 1300-1400MHz, Insertion Loss(f0): 3.0dB, SMA Female	Rev.1.0