

Power Amplifier

0.5-6GHz/35dB Gain/30dBm Psat

Model: TLPA0.5G6G-35-30

TLPA0.5G6G-35-30 is a power amplifier with a typical small signal gain of 35 dB and a minimum Psat of 30 dBm across the frequency range of 0.5 to 6 GHz. The DC power requirement for the amplifier is +12 VDC/280 mA. The input and output port configuration offers coax adapter structure with SMA female.

Features:

- Frequency range: 0.5-6GHz
- Gain: 35dB Typ
- Output Power Psat: 30dBm Min
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Cellular
- PCN
- GSM
- ISM
- Lab Test

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	0.5		6	GHz
小信号增益 Small Signal Gain		35		dB
增益平坦度 Gain Flatness		±2.5		dB
线性输出功率 Output P1dB	28			dBm
饱和输出功率 Output Psat	30			dBm
输入驻波 Input VSWR		2	2.2	:1
直流电压 DC Voltage		+12		V DC
直流电流 DC Supply Current		280		mA
阻抗 Impedance		50		Ohms

机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	SMA Female/SMA Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	100*70*12	mm

绝对最大值 Absolute Maximum Ratings:


参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	TBD
输入功率 RF Input Power	0 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V



Simple 220V System
Available SAC option

外形图 Outline Drawing:

Unit:mm; Tolerance:±0.1mm



*****Heat Sink Required During Operation**



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-40		+60	°C
存储温度 Non-operating Temperature*	-50		+70	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	50,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			


*Note: For a wider temperature range, please consult the manufacturer.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLPA0.5G6G-35-30	Power amplifier 0.5-6GHz, Gain:35dB,Psat:30dBm,+12V DC,Without Heatsink	Rev.1.2
TLPA0.5G6G-35-30-HS	Power amplifier 0.5-6GHz, Gain:35dB,Psat:30dBm,+12V DC,With Heatsink	Rev.1.2

典型曲线 Typical Performance Data:


VSWR&Small Signal Gain vs Frequency




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:


Gain vs Output Power



Small Signal Gain vs Frequency



P1dB vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.