

Coaxial Band-pass Filter

750-1250 MHz/SMA Female

Model: TLBF-750M-1250M-S

TLBF-750M-1250M-S is a coaxial band-pass filter with a passband frequency from 750 to 1250 MHz and a rejection frequencies from DC to 584 MHz and from 1416 to 6000 MHz. The maximum insertion loss of the filter is 2.5 dB and the minimum rejection is 50 dB.

Features:

- Passband Frequency Range 750 to 1250 MHz
- High Rejection
- Steep Rejection Skirts

Applications:

- Instrumentations
- Radar Systems
- System Integrations


电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
通带频率范围 Passband Frequency range	750		1250	MHz
带宽 Band Width		500		MHz
通带插损 Passband Insertion Loss			2.5	dB
驻波 VSWR			1.5	:1
带外抑制 Rejection@DC-584MHz&1416-6000MHz	50			dB
耐受功率 Power Handling			50	W
阻抗 Impedance	50			Ohms

环境和机械特性 Envriionmental And Physical Characteristics:

类型 Description	参数 Parameter	单位 Units
操作温度 Operating Temperature	-40 To +70	°C
存储温度 Storage Temperature	-55 to +85	°C
接口 Connectors	SMA Female	
尺寸 Size	12*12*40.4	mm

外形图 Outline Drawing: Unit:mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLBF-750M-1250M-S	Coaxial Band-pass Filter, Passband frequency range: 750-1250MHz, Passband Insertion Loss: 2.5dB, SMA Female	Rev.1.0