

Coaxial Band-pass Filter

Center Frequency 1300 MHz/SMA Female

Model: TLBF-1300M-5M-L

TLBF-1300M-5M-L is a coaxial band-pass filter with a passband center frequency at 1300 MHz and a rejection frequencies from DC to 1200 MHz and point at 1400 MHz. The maximum insertion loss of the filter is 5.0 dB and the minimum rejection is 50 dB.

Features:

- Passband Center Frequency 1300 MHz
- High Rejection
- Steep Rejection Skirts

Applications:

- Instrumentations
- Radar Systems
- System Integrations


电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
通带频率范围 Passband Frequency range	1297.5		1302.5	MHz
带宽 Band Width			5	MHz
插损 Insertion Loss(f0)			5.0	dB
带内纹波 Pass Band Ripple			4.2	dB
驻波 VSWR			1.6	:1
带外抑制 Rejection@DC-1200MHz&1400MHz	50			dB
耐受功率 Power Handling			2	W
阻抗 Impedance	50			Ohms

环境和机械特性 Envirionmental And Physical Characteristics:

类型 Description	参数 Parameter	单位 Units
操作温度 Operating Temperature	-40 To +70	℃
接口 Connectors	SMA Female	
尺寸 Size	10*12*40.4	mm

外形图 Outline Drawing: Unit:mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLBF-1300M-5M-L	Coaxial Band-pass Filter, Passband center frequency: 1300MHz, Insertion Loss(f0): 5.0dB, SMA Female	Rev.1.0