Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

Flexible Waveguide Cable

WR-6.5/110-170GHz

Model: FW-WR06WR06-0.2m

FW-WR06WR06-0.2m is a flexible waveguide cable that covers the frequency range of 110 to 170 GHz. The flexible waveguide cable includes two WR-6.5 waveguide ports with UG-387/U-M anti-cocking flange.

Features:

- Operating Frequency 110 to 170GHz
- VSWR: 1.9:1 Typ
- Insertion loss: 8dB Typ
- Low cost
- Fast delivery time

Applications:

- Test Lab
- Instrumentations
- System setups

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency Range	110		170	GHz
驻波 VSWR		1.9		:1
插损 Insertion Loss		8		dB
耐功率 Power Handling		4 CW		W

环境和机械特性 Envrionmental And Physical Characteristics:


参数 Parameter	指标 Value	单位 Units
操作温度 Operating Temerature	+25	℃
存储温度 Non-operating Temperature	-55~+165	℃
最小弯曲半径 Minimum Bending Radius	25	mm
波导接口 Waveguide Connector	WR-6.5/UG-387/U	
长度 Length*	0.2	m


*Note:Length can be customized.

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

外形图 Outline Drawing:

Unit:mm; Tolerance:±0.1mm





ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description
FW-WR06WR06-0.2m	Flexible Waveguide Cable, 110-170GHz, WR-6.5, Length can be customized