泰莱微波
Talent Microwave

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

Coax Directional Coupler

6-50GHz/20dB Coupling/2.4mm Female

Model: TC-60500-20-2.4

TC-60500-20-2.4 is a coaxial directional coupler that delivers a 20 dB nominal coupling level and 10 dB minimum directivity across the full frequency range from 6 to 50 GHz. It is a three-port passive device that can couple a portion of the power from the main transmission line to the auxiliary line in a directional manner.

Features:

- Output Frequency:6-50GHz
- Coupling: 20dB Typ
- Stackable mechanical design
- Low Insertion Loss
- Moderate Directivity
- 50 Ohm Matched Input / Output

Applications:

- Test Labs
- Instrumentations
- Sub-assemblies

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
工作频率 Frequency Range	6		50	GHz
插入损耗 Insertion Loss (不含耦合插损 Excl Coupling)		2.0	2.3	dB
耦合度 Coupling		20±1.2		dB
方向性 Directivity	10	12		dB
耐功率 Power Handling			30	W
驻波 VSWR			1.9	:1
阻抗 Impedance		50		Ohms


机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input/Output Connector	2.4mm Female/2.4mm Female	
尺寸 Size	26*15*11	mm

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

外形图 Outline Drawing:

Unit:mm; Tolerance:±0.1mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
温度范围 Temperature Range	-45		+85	℃
相对湿度 Relative humidity	100% RH at 35c, 95%RH at 40℃			%
海拔 Altitude	50,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TC-60500-20-2.4	Coaxial Directional Coupler 6-50GHz, Coulping:20dB, 2.4mm Female	Rev.1.0