泰莱微波 Talent Microwave

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

Equalizer

6-18GHz/6dB, Slope

Model: TLME-6G18G-06

The TLME-6G18G-06 is an equalizer. It is a positive gain slope equalizer designed to pass 6 to 18 GHz. Equalization can be applied to reduce low pass filtering effects in both RF/microwave and high speed digital systems.

Features:

- Frequency range: 6-18 GHz
- Good gain equalization
- 2.92mmll Size and simple to use
- Excellent return loss

Applications:

- Cable or Waveguide Loss Compensation
- Amplifier Flatness Compensation
- Microwave Radio
- RF Transceivers
- Telecom Infrastructure

电气特性 Electrical Characteristics:

参数 Parameter		Min	Typ	Max	单位 Units
频率范围 Frequency range		6		18	GHz
插损 Insertion Loss	@6GHz		7		dB
	@18GHz		1		
回波损耗 Return Loss			-15		dB
耐受功率 Power Handling			30		dBm
阻抗 Impedance			50		Ohms

机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	2.92mm	
长度 Length	42.2	mm

泰莱微波 Talent Microwave
Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

外形图 Outline Drawing:

Unit:mm; Tolerance:±0.1mm



TLME-6G18G-06



TLME-6G18G-06-MM



TLME-6G18G-06-FF



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-40		+70	℃
存储温度 Non-operating Temperature	-55		+85	℃
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLME-6G18G-06	Equalizer, 6-18GHz, Insertion loss: 7dB@6GHz; 1dB@18GHz; 2.92mm Male/2.92mm Female	Rev.1.0
TLME-6G18G-06-MM	Equalizer, 6-18GHz, Insertion loss: 7dB@6GHz; 1dB@18GHz; 2.92mm Male/2.92mm Male	Rev.1.0
TLME-6G18G-06-FF	Equalizer, 6-18GHz, Insertion loss: 7dB@6GHz; 1dB@18GHz; 2.92mm Female/2.92mm Female	Rev.1.0