Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

Coax Directional Coupler

0.3-0.4GHz/10dB Coupling/SMA Female

Model: TC-0304-10S

TC-0304-10S is a coaxial directional coupler that delivers a 10 dB nominal coupling level and 20 dB minimum directivity across the full frequency range from 0.3 to 4 GHz. It is a three-port passive device that can couple a portion of the power from the main transmission line to the auxiliary line in a directional manner.

Features:

- Output Frequency: 0.3-0.4GHz
- Coupling: 10dB Typ
- Stackable mechanical design
- Low Insertion Loss
- Moderate Directivity
- 50 Ohm Matched Input / Output

Applications:

- Test Labs
- Instrumentations
- Sub-assemblies

Electrical Characteristics:

Parameter	Min	Typ	Max	Units
Frequency Range	0.3		0.4	GHz
Insertion Loss (Excl Coupling)			1.2	dB
Coupling		10±1		dB
Directivity	20			dB
Power Handling			30	W
VSWR		1.3		:1
Impedance		50		Ohms


Mechanical Specifications:

Parameter	Value	Units
Operating Temperature	-55-+85	℃
Input/Output Connector	SMA Female/SMA Female	
Size	106*19*15	mm

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

Outline Drawing:

Unit:mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

Ordering Information:

Base Number	Description	Revision
TC-0304-10S	Coaxial Directional Coupler 0.3-0.4GHz, Coulping:10dB, SMA Female	Rev.1.0