Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

Coax Directional Coupler

0.8-2.5GHz/6dB Coupling/N Female

Model: TC-0825-6N

TC-0825-6N is a coaxial directional coupler that delivers a 6 dB nominal coupling level and 20 dB minimum directivity across the full frequency range from 0.8 to 2.5 GHz. It is a three-port passive device that can couple a portion of the power from the main transmission line to the auxiliary line in a directional manner.

Features:

- Output Frequency: 0.8-2.5GHz
- Coupling: 6dB Typ
- Stackable mechanical design
- Low Insertion Loss
- Moderate Directivity
- 50 Ohm Matched Input / Output

Applications:

- Test Labs
- Instrumentations
- Sub-assemblies

Electrical Characteristics:

Parameter	Min	Typ	Max	Units
Frequency Range	0.8		2.5	GHz
Insertion Loss (Excl Coupling)			1.6	dB
Coupling		6±1		dB
Directivity	20			dB
Power Handling			200	W
VSWR			1.3	:1
Impedance		50		Ohms


Mechanical Specifications:

Parameter	Value	Units
Operating Temperature	-55-+85	℃
Input/Output Connector	N Female/N Female	
Size	120*40*17	mm

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

Outline Drawing:

Unit:mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

Ordering Information:

Base Number	Description	Revision
TC-0825-6N	Coaxial Directional Coupler 0.8-2.5GHz, Coulping:6dB, N Female	Rev.1.0