泰莱微波
Talent Microwave

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

Coax Directional Coupler

1-4GHz/40dB Coupling/SMA Female

Model: TC-1040-40S

TC-1040-40S is a coaxial directional coupler that delivers a 40 dB nominal coupling level and 15 dB minimum directivity across the full frequency range from 1 to 4 GHz. It is a three-port passive device that can couple a portion of the power from the main transmission line to the auxiliary line in a directional manner.

Features:

- Output Frequency: 1-4GHz
- Coupling: 40dB Typ
- Stackable mechanical design
- Low Insertion Loss
- Moderate Directivity
- 50 Ohm Matched Input / Output

Applications:

- Test Labs
- Instrumentations
- Sub-assemblies

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
工作频率 Frequency Range	1		4	GHz
插入损耗 Insertion Loss (不含耦合插损 Excl Coupling)			0.4	dB
耦合度 Coupling		40±1.5		dB
方向性 Directivity	15			dB
耐功率 Power Handling			30	W
驻波 VSWR			1.3	:1
阻抗 Impedance		50		Ohms

机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
操作温度 Operating Temperature	-55-+85	℃
输入/输出接口 Input/Output Connector	SMA Female/SMA Female	
尺寸 Size	73*20*11	mm

泰莱微波
Talent Microwave
Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

外形图 Outline Drawing: Unit:mm





ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TC-1040-40S	Coaxial Directional Coupler 1-4GHz, Coulping:40dB, SMA Female	Rev.1.0