泰莱微波
Talent Microwave

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

Coax Directional Coupler

0.3-18GHz/20dB Coupling/SMA Female

Model: TC-03180-20S

TC-03180-20S is a coaxial directional coupler that delivers a 20 dB nominal coupling level and 10 dB minimum directivity across the full frequency range from 0.3 to 18 GHz. It is a three-port passive device that can couple a portion of the power from the main transmission line to the auxiliary line in a directional manner.

Features:

- Output Frequency: 0.3-18GHz
- Coupling: 20dB Typ
- Stackable mechanical design
- Low Insertion Loss
- Moderate Directivity
- 50 Ohm Matched Input / Output

Applications:

- Test Labs
- Instrumentations
- Sub-assemblies

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
工作频率 Frequency Range	0.3		18	GHz
插入损耗 Insertion Loss (不含耦合插损 Excl Coupling)		2.3	2.6	dB
耦合度 Coupling		20±1.6		dB
方向性 Directivity	10	12		dB
耐功率 Power Handling			30	W
驻波 VSWR			1.6	:1
阻抗 Impedance		50		Ohms


机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
操作温度 Operating Temperature	-55-+85	℃
输入/输出接口 Input/Output Connector	SMA Female/SMA Female	
尺寸 Size	206*18*11	mm

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

外形图 Outline Drawing:

Unit:mm





ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TC-03180-20S	Coaxial Directional Coupler 0.3-18GHz, Coulping:20dB, SMA Female	Rev.1.0