泰莱微波
Talent Microwave

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

# Coax Directional Coupler

## 1-18GHz/15dB Coupling/SMA Female

## Model: TC-10180-15S

TC-10180-15S is a coaxial directional coupler that delivers a 15 dB nominal coupling level and 12 dB minimum directivity across the full frequency range from 1 to 18 GHz. It is a three-port passive device that can couple a portion of the power from the main transmission line to the auxiliary line in a directional manner.

### Features:

- Output Frequency: 1-18GHz
- Coupling: 15dB Typ
- Stackable mechanical design
- Low Insertion Loss
- Moderate Directivity
- 50 Ohm Matched Input / Output

### Applications:

- Test Labs
- Instrumentations
- Sub-assemblies

### Electrical Characteristics:

| Parameter | Min | Typ | Max | Units |
|---|---|---|---|---|
| Frequency Range | 1 | | 18 | GHz |
| Insertion Loss (Excl Coupling) | | 0.5 | 0.7 | dB |
| Coupling | | 15±1 | | dB |
| Directivity | 12 | 15 | | dB |
| Power Handling | | | 30 | W |
| VSWR | | | 1.5 | :1 |
| Impedance | | 50 | | Ohms |


### Mechanical Specifications:

| Parameter | Value | Units |
|---|---|---|
| Operating Temperature | -55-+85 | ℃ |
| Input/Output Connector | SMA Female/SMA Female | |
| Size | 73*15*11 | mm |

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

## Outline Drawing:

Unit:mm




ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

## Ordering Information:

| Base Number | Description | Revision |
|---|---|---|
| TC-10180-15S | Coaxial Directional Coupler<br>1-18GHz, Coulping:15dB, SMA Female | Rev.1.0 |