泰莱微波
Talent Microwave

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

Coax Directional Coupler

1-18GHz/20dB Coupling/SMA Female

Model: TC-10180-20S-50W

TC-10180-20S-50W is a coaxial directional coupler that delivers a 20 dB nominal coupling level and 12 dB minimum directivity across the full frequency range from 1 to 18 GHz. It is a three-port passive device that can couple a portion of the power from the main transmission line to the auxiliary line in a directional manner.

Features:

- Output Frequency: 1-18GHz
- Coupling: 20dB Typ
- Stackable mechanical design
- Low Insertion Loss
- Moderate Directivity
- 50 Ohm Matched Input / Output

Applications:

- Test Labs
- Instrumentations
- Sub-assemblies

Electrical Characteristics:

Parameter	Min	Typ	Max	Units
Frequency Range	1		18	GHz
Insertion Loss (Excl Coupling)		0.8		dB
Coupling		20±1.2		dB
Directivity	12	15		dB
Power Handling			50	W
VSWR			1.6	:1
Impedance		50		Ohms


Mechanical Specifications:

Parameter	Value	Units
Operating Temperature	-55-+85	℃
Input/Output Connector	SMA Female/SMA Female	
Size	73*15*11	mm

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

Outline Drawing:

Unit:mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

Ordering Information:

Base Number	Description	Revision
TC-10180-20S-50W	Coaxial Directional Coupler 1-18GHz, Coulping:20dB, SMA Female	Rev.1.0