Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

Coax Directional Coupler

1-40GHz/30dB Coupling/2.92mm Female

Model: TC-10400-30K

TC-10400-30K is a coaxial directional coupler that delivers a 30 dB nominal coupling level and 8 dB minimum directivity across the full frequency range from 1 to 40 GHz. It is a three-port passive device that can couple a portion of the power from the main transmission line to the auxiliary line in a directional manner.

Features:

- Output Frequency: 1-40GHz
- Coupling: 30dB Typ
- Stackable mechanical design
- Low Insertion Loss
- Moderate Directivity
- 50 Ohm Matched Input / Output

Applications:

- Test Labs
- Instrumentations
- Sub-assemblies

Electrical Characteristics:

Parameter	Min	Typ	Max	Units
Frequency Range	1		40	GHz
Insertion Loss (Excl Coupling)		1.8	2.0	dB
Coupling		30±1.8		dB
Directivity	8	12		dB
Power Handling			30	W
VSWR			1.7	:1
Impedance		50		Ohms


Mechanical Specifications:

Parameter	Value	Units
Operating Temperature	-55-+85	℃
Input/Output Connector	2.92mm Female/2.92mm Female	
Size	84*15*11	mm

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

Outline Drawing:

Unit:mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

Ordering Information:

Base Number	Description	Revision
TC-10400-30K	Coaxial Directional Coupler 1-40GHz, Coulping:30dB, 2.92mm Female	Rev.1.0