泰莱微波
Talent Microwave

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

Coax Directional Coupler

6-40GHz/10dB Coupling/2.92mm Female

Model: TC-60400-10K

TC-60400-10K is a coaxial directional coupler that delivers a 10 dB nominal coupling level and 10 dB minimum directivity across the full frequency range from 6 to 40 GHz. It is a three-port passive device that can couple a portion of the power from the main transmission line to the auxiliary line in a directional manner.

Features:

- Output Frequency: 6-40GHz
- Coupling: 10dB Typ
- Stackable mechanical design
- Low Insertion Loss
- Moderate Directivity
- 50 Ohm Matched Input / Output

Applications:

- Test Labs
- Instrumentations
- Sub-assemblies

Electrical Characteristics:

Parameter	Min	Typ	Max	Units
Frequency Range	6		40	GHz
Insertion Loss (Excl Coupling)			1.7	dB
Coupling		10±1		dB
Directivity	10			dB
Power Handling			30	W
VSWR			1.6	:1
Impedance		50		Ohms


Mechanical Specifications:

Parameter	Value	Units
Operating Temperature	-55-+85	℃
Input/Output Connector	2.92mm Female/2.92mm Female	
Size	28*15*11	mm

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

Outline Drawing:

Unit:mm






ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.


Ordering Information:


Base Number	Description	Revision
TC-60400-10K	Coaxial Directional Coupler 6-40GHz, Coulping:10dB, 2.92mm Female	Rev.1.0


Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com


Typical Performance Data:











Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.