泰莱微波
Talent Microwave

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

Coax Directional Coupler

0.698-2.7GHz/3dB Coupling/N Femal

Model: TC-06987200-3N-200W(2 in and 1 out）

TC-06982700-3N-200W(2 in and 1 out) is a coaxial directional coupler that delivers a 3 dB nominal coupling across the full frequency range from 0.698 to 2.7 GHz. It is a three-port passive device that can couple a portion of the power from the main transmission line to the auxiliary line in a directional manner.

Features:

- Output Frequency: 0.698-2.7GHz
- Coupling: 3dB Typ
- Stackable mechanical design
- Low Insertion Loss
- Moderate Directivity
- 50 Ohm Matched Input / Output

Applications:

- Test Labs
- Instrumentations
- Sub-assemblies

Electrical Characteristics:

Parameter	Min	Typ	Max	Units
Frequency Range	0.698		2.7	GHz
Insertion Loss (Excl Coupling)			0.8	dB
Coupling		3		dB
Isolation	23			dB
Amplitude Balance			±0.8	dB
Power Handling			200(2inX100W)	W
VSWR			1.3	:1
Impedance		50		Ohms


Mechanical Specifications:

Parameter	Value	Units
Operating Temperature	-55-+85	℃
Input/Output Connector	N Female/N Female	
Size	142*80*44.5	mm

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

Outline Drawing:

Unit:mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

Ordering Information:

Base Number	Description	Revision
TC-06982700-3N-200W(2 in and 1out)	Coaxial Directional Coupler 0.698-2.7GHz, Coulping:3dB, N Female	Rev.1.0