泰莱微波 Talent Microwave

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

Coax Dual-Directional Coupler

1-6GHz/10dB Coupling/SMA Female

Model: TDC-1060-10S

TDC-1060-10S is a coax dual-directional coupler that delivers a 10 dB nominal coupling level and 18 dB minimum directivity across the full frequency range from 1 to 6GHz. It is a four-port passive device that can couple a portion of the power from the main transmission line to the auxiliary line in a directional manner.

Features:

- Output Frequency: 1-6GHz
- Max Power: 50W
- Stackable mechanical design
- Low Insertion Loss
- Moderate Directivity
- 50 Ohm Matched Input / Output

Applications:

- Test Labs
- Instrumentations
- Sub-assemblies

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
工作频率 Frequency Range	1		6	GHz
插入损耗 Insertion Loss(Excl coupling)		0.8	1.5	dB
耦合度 Coupling		10±1.2		dB
方向性 Directivity	18	20		dB
主线驻波 Main Line VSWR			1.3	:1
耐功率 Power Handling			50	W
阻抗 Impedance		50		Ohms

机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
操作温度 Operating Temperature	-45 to +85	℃
RF接口 RF Connector	SMA Female	
尺寸 Size	73*24*11	mm

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

外形图 Outline Drawing:

Unit:mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TDC-1060-10S	Coax Dual-Directional Coupler 1-6GHz, Coulping:10dB, SMA Female	Rev.1.0