泰莱微波 Talent Microwave

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

Coax Dual-Directional Coupler

18-40GHz/40dB Coupling/2.92mm Female

Model: TDC-180400-40K

TDC-180400-40K is a coax dual-directional coupler that delivers a 40 dB nominal coupling level and 8 dB minimum directivity across the full frequency range from 18 to 40GHz. It is a four-port passive device that can couple a portion of the power from the main transmission line to the auxiliary line in a directional manner.

Features:

- Output Frequency: 18-40GHz
- Max Power: 20W
- Stackable mechanical design
- Low Insertion Loss
- Moderate Directivity
- 50 Ohm Matched Input / Output

Applications:

- Test Labs
- Instrumentations
- Sub-assemblies

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
工作频率 Frequency Range	18		40	GHz
插入损耗 Insertion Loss(Excl coupling)		1.0	1.2	dB
耦合度 Coupling		40±1.8		dB
方向性 Directivity	8	10		dB
主线驻波 Main Line VSWR			1.8	:1
耐功率 Power Handling			20	W
阻抗 Impedance		50		Ohms


机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
操作温度 Operating Temperature	-45 to +85	℃
RF接口 RF Connector	2.92mm Female	
尺寸 Size	52*17*11	mm

泰莱微波
Talent Microwave
Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

外形图 Outline Drawing:

Unit:mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TDC-180400-40K	Coax Dual-Directional Coupler 18-40GHz, Coulping:40dB, 2.92mm Female	Rev.1.0