泰莱微波 Talent Microwave

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

High Power Directional Coupler

100-500MHz/30dB Coupling/N Female Model: TC-0105-30N-500W

TC-0105-30N-500W is a high power directional coupler that delivers a 30 dB nominal coupling level and 20 dB minimum directivity across the full frequency range from 100 to 500MHz. It is a three-port passive device that can couple a portion of the power from the main transmission line to the auxiliary line in a directional manner.

Features:

- Output Frequency: 100-500MHz
- Max Power: 500W
- Stackable mechanical design
- Low Insertion Loss
- Moderate Directivity
- 50 Ohm Matched Input / Output

Applications:

- Test Labs
- Instrumentations
- Sub-assemblies

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
工作频率 Frequency Range	100		500	MHz
插入损耗 Insertion Loss(Excl coupling)		0.3	0.4	dB
耦合度 Coupling		30±1.3		dB
方向性 Directivity	20	22		dB
主线驻波 Main Line VSWR			1.3	:1
耐功率 Power Handling			500	W
阻抗 Impedance		50		Ohms


机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
操作温度 Operating Temperature	-45 to +85	℃
RF接口 RF Connector	N Female/Male	
耦合接口 Coupling Connector	N Female	
尺寸 Size	318*39*27	mm

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

外形图 Outline Drawing:

Unit:mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TC-0105-30N-500W	High Power Directional Coupler 100-500MHz, Coulping:30dB, N Female/Male	Rev.1.0