泰莱微波 Talent Microwave
Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

High Power Dual-Directional Coupler

0.08-1GHz/45dB Coupling/SMA Female Model: TDC-80M010-45S-100

TDC-80M010-45S-100is a high power dual-directional coupler that delivers a 45 dB nominal coupling level and 18 dB minimum directivity across the full frequency range from 0.08 to1GHz. It is a four-port passive device that can couple a portion of the power from the main transmission line to the auxiliary line in a directional manner.

Features:

- Output Frequency: 0.08-1GHz
- Max Power: 100W
- Stackable mechanical design
- Low Insertion Loss
- Moderate Directivity
- 50 Ohm Matched Input / Output

Applications:

- Test Labs
- Instrumentations
- Sub-assemblies

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
工作频率 Frequency Range	0.08		1	GHz
插入损耗 Insertion Loss(Excl coupling)			0.5	dB
耦合度 Coupling		45±1.2		dB
方向性 Directivity	18			dB
主线驻波 Main Line VSWR			1.3	:1
耐功率 Power Handling		100		W
阻抗 Impedance		50		Ohms


机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
RF接口 RF Connector	SMA Female	
耦合接口 Coupling Connector	SMA Female	
尺寸 Size	85*79*12	mm

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

外形图 Outline Drawing:

Unit:mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TDC-80M010-45S-100	High Power Dual-Directional Coupler 0.08-1GHz, Coulping:45dB, SMA Female	Rev.1.0