Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

High Power Dual-Directional Coupler

0.08-1GHz/50dB Coupling/L29 Female Model: TDC-00810-50L29-2000W

TDC-00810-50L29-2000W is a high power dual-directional coupler that delivers a 50 dB nominal coupling level and 18 dB minimum directivity across the full frequency range from 0.08 to1GHz. It is a four-port passive device that can couple a portion of the power from the main transmission line to the auxiliary line in a directional manner.

Features:

- Output Frequency: 0.08-1GHz
- Max Power: 2000W
- Stackable mechanical design
- Low Insertion Loss
- Moderate Directivity
- 50 Ohm Matched Input / Output

Applications:

- Test Labs
- Instrumentations
- Sub-assemblies

Electrical Characteristics:

Parameter	Min	Typ	Max	Units
Frequency Range	0.08		1	GHz
Insertion Loss(Excl coupling)			0.3	dB
Coupling		50±1		dB
Directivity	18			dB
Main Line VSWR			1.3	:1
Power Handling			2000	W
Impedance		50		Ohms


Mechanical Specifications:

Parameter	Value	Units
Operating Temperature	-40 to +70	℃
RF Connector	L29 Female	
Coupling Connector	N Female	
Size	85*48*32	mm

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

Outline Drawing:

Unit:mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

Ordering Information:

Base Number	Description	Revision
TDC-00810-50L29-2000W	High Power Dual-Directional Coupler 0.08-1GHz, Coulping:50dB, L29 Female	Rev.1.0