泰莱微波
Talent Microwave

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

High Power Dual-Directional Coupler

2-3GHz/50dB Coupling/N Female

Model: TDC-2030-50N-300W

TDC-2030-50N-300W is a high power dual-directional coupler that delivers a 50 dB nominal coupling level and 15 dB minimum directivity across the full frequency range from 2 to 3GHz. It is a four-port passive device that can couple a portion of the power from the main transmission line to the auxiliary line in a directional manner.

Features:

- Output Frequency: 2-3GHz
- Max Power: 300W
- Stackable mechanical design
- Low Insertion Loss
- Moderate Directivity
- 50 Ohm Matched Input / Output

Applications:

- Test Labs
- Instrumentations
- Sub-assemblies

Electrical Characteristics:

Parameter	Min	Typ	Max	Units
Frequency Range	2		3	GHz
Insertion Loss(Excl coupling)			0.4	dB
Coupling		50±2		dB
Directivity	15			dB
Main Line VSWR			1.3	:1
Power Handling			300	W
Impedance		50		Ohms


Mechanical Specifications:

Parameter	Value	Units
Operating Temperature	-30 to +70	℃
RF Connector	N Female	
Coupling Connector	N Female	
Size	74*52*20	mm

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

Outline Drawing:

Unit:mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

Ordering Information:

Base Number	Description	Revision
TDC-2030-50N-300W	High Power Dual-Directional Coupler 2-3GHz, Coulping:50dB, N Female	Rev.1.0